## FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO Hobas Pipe USA, Inc.

AUTHORIZING THE OPERATION OF
Houston Plant
Plastics Pipe and Pipe Fitting Manufacturing

LOCATED AT

Harris County, Texas
Latitude 29° 59′ 53″ Longitude 95° 23′ 15″
Regulated Entity Number: RN102540812

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No:	O2766	Issuance Date:	July 27, 2022	
			•	
For the Co	mmission			

# **Table of Contents**

Section	Page
General Terms and Conditions	1
Special Terms and Conditions:	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting	
New Source Review Authorization Requirements	6
Compliance Requirements	7
Protection of Stratospheric Ozone	
Permit Location	8
Permit Shield (30 TAC § 122.148)	8
Attachments	10
Applicable Requirements Summary	11
Permit Shield	22
New Source Review Authorization References	24
Appendix A	29
Acronym List	30

#### **General Terms and Conditions**

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

#### **Special Terms and Conditions:**

#### Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

- 1. Permit holder shall comply with the following requirements:
  - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
  - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
  - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
  - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
  - E. Emission units subject to 40 CFR Part 63, Subparts WWWW, ZZZZ, and DDDDD as identified in the attached Applicable Requirements Summary table are subject to 30 TAC

- Chapter 113, Subchapter C, §113.1060, §113.1090, and §113.1130, respectively, which incorporate the 40 CFR Part 63 Subparts by reference.
- 2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
  - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
  - B. Title 30 TAC § 101.3 (relating to Circumvention)
  - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
  - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
  - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
  - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
  - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
  - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
  - I. Title 30 TAC § 101.222 (relating to Demonstrations)
  - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
- 3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
  - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
    - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
    - (ii) Title 30 TAC § 111.111(a)(1)(E)
    - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
    - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that

does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
  - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
  - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is

determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.
- B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:
  - (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
  - (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
  - (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
    - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
    - (2) Records of all observations shall be maintained.
    - Visible emissions observations of air emission sources or enclosed (3)facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

- (4) Compliance Certification:
  - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A).
  - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- C. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
  - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
  - (ii) Sources with an effective stack height (h<sub>e</sub>) less than the standard effective stack height (H<sub>e</sub>), must reduce the allowable emission level by multiplying it by [h<sub>e</sub>/H<sub>e</sub>]<sup>2</sup> as required in 30 TAC § 111.151(b)
  - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- 4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: Storage of Volatile Organic Compounds, the permit holder shall comply with the requirements of 30 TAC § 115.112(e)(1).
- 5. The permit holder shall comply with the following requirements of 30 TAC Chapter 117:
  - A. For stationary reciprocating engines exempt from Subchapter D, Division 1 at minor sources of NO<sub>x</sub> under 30 TAC § 117.2003(a), the permit holder shall comply with 30 TAC §§ 117.2030(c), 117.2035(g), 117.2045(b) and 117.2045(c).
- 6. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
  - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
  - B. Title 40 CFR § 60.8 (relating to Performance Tests)
  - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)

- D. Title 40 CFR § 60.12 (relating to Circumvention)
- E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
- F. Title 40 CFR § 60.14 (relating to Modification)
- G. Title 40 CFR § 60.15 (relating to Reconstruction)
- H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
- 7. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
- 8. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

#### **New Source Review Authorization Requirements**

- 9. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule (including the terms, conditions, monitoring, recordkeeping, and reporting identified in registered PBRs and permits by rule identified in the PBR Supplemental Tables dated June 2, 2023 in the application for project 34014), standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
  - A. Are incorporated by reference into this permit as applicable requirements
  - B. Shall be located with this operating permit
  - C. Are not eligible for a permit shield
- 10. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
- 11. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating

noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

- 12. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
  - A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit
  - B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit
  - C. Requirements of the non-rule Air Quality Standard Permit for Pollution Control Projects

#### **Compliance Requirements**

- 13. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
- 14. Use of Emission Credits to comply with applicable requirements:
  - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
    - (i) Title 30 TAC Chapter 115
    - (ii) Title 30 TAC Chapter 117
    - (iii) Offsets for Title 30 TAC Chapter 116
  - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
    - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)
    - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
    - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)
    - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
    - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
- 15. Use of Discrete Emission Credits to comply with the applicable requirements:

- A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
  - (i) Title 30 TAC Chapter 115
  - (ii) Title 30 TAC Chapter 117
  - (iii) If applicable, offsets for Title 30 TAC Chapter 116
  - (iv) Temporarily exceed state NSR permit allowables
- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
  - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
  - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
  - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
  - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
  - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

#### **Protection of Stratospheric Ozone**

- 16. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
  - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

#### **Permit Location**

17. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

#### Permit Shield (30 TAC § 122.148)

18. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than

90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

### **Attachments**

**Applicable Requirements Summary** 

**Permit Shield** 

**New Source Review Authorization References** 

Unit Summary	12
Applicable Requirements Summary	15

Note: A "none" entry may be noted for some emission sources in this permit's "Applicable Requirements Summary" under the heading of "Monitoring and Testing Requirements" and/or "Recordkeeping Requirements" and/or "Reporting Requirements." Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

## **Unit Summary**

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
BOILER	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
CLEANUP	CLEANING/DEPAINTING OPERATION	N/A	R5461	30 TAC Chapter 115, Subchapter E, Division 6	No changing attributes.
DTANK	LOADING/UNLOADING OPERATIONS	N/A	R5217	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
DTANK	STORAGE TANKS/VESSELS	N/A	R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
FWC	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5122	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
FWC	REINFORCED PLASTIC COMPOSITES PRODUCTION	N/A	63WWW2	40 CFR Part 63, Subpart WWWW	No changing attributes.
FWP1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5122	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
FWP1	MISCELLANEOUS UNITS	N/A	63WWWW	40 CFR Part 63, Subpart WWWW	No changing attributes.
FWPSTYTK	LOADING/UNLOADING OPERATIONS	N/A	R5127	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
FWPSTYTK	STORAGE TANKS/VESSELS	N/A	R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GEN	SRIC ENGINES	N/A	63ZZZZ1	40 CFR Part 63, Subpart ZZZZ	Service Type = Emergency use where the RICE does not operate as specified in 40 CFR

## **Unit Summary**

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					§63.6640(f)(2)(ii) and (iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).
GEN	SRIC ENGINES	N/A	63ZZZZ3	40 CFR Part 63, Subpart ZZZZ	Service Type = Limited use.
GRPCASTMIX	PCASTMIX STORAGE TANKS/VESSELS		R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPCASTRTK	RPCASTRTK LOADING/UNLOADING OPERATIONS		R5217	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
GRPCASTRTK	STORAGE TANKS/VESSELS	RTK1, RTK2, RTK3, RTK4, RTK5, RTK6, RTK7, RTK8	R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPCFLEXTK	LOADING/UNLOADING OPERATIONS	RFLXTK1, RFLXTK2, RFLXTK3, RFLXTK4	R5217	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
GRPCFLEXTK	STORAGE TANKS/VESSELS	RFLXTK1, RFLXTK2, RFLXTK3, RFLXTK4	R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPFWPMIX	STORAGE TANKS/VESSELS	FWP-MIXER1, FWP-MIXER2, FWP-MIXER3, FWP-MIXER4	R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPFWPRTK	LOADING/UNLOADING OPERATIONS	FWPRTK1, FWPRTK2, FWPRTK3	R5217	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.

## **Unit Summary**

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPFWPRTK	STORAGE TANKS/VESSELS	FWPRTK1, FWPRTK2, FWPRTK3	R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPNCMIX	STORAGE TANKS/VESSELS	NCMIX1, NCMIX2, NCMIX3, NCMIX4	R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPNCRTK	CRTK LOADING/UNLOADING NC OPERATIONS NC		R5217	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
GRPNCRTK	STORAGE TANKS/VESSELS	NCRTK1, NCRTK2, NCRTK3	R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MAIN	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5122	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MAIN	REINFORCED PLASTIC COMPOSITES PRODUCTION	N/A	63WWW1	40 CFR Part 63, Subpart WWWW	No changing attributes.
NCPIPE	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5122	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NCPIPE	REINFORCED PLASTIC COMPOSITES PRODUCTION	N/A	63WWW3	40 CFR Part 63, Subpart WWWW	No changing attributes.

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
BOILER	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)- Table 3.1 § 63.7500(a)(1) § 63.7500(a)(3) § 63.7500(e) § 63.7540(a) § 63.7540(a)(10)(ii) § 63.7540(a)(10)(iii) § 63.7540(a)(10)(iv) § 63.7540(a)(10)(v) [G]§ 63.7540(a)(10)(vi) § 63.7540(a)(10)(vi) § 63.7540(a)(10)(vi) § 63.7540(a)(10)(vi) § 63.7540(a)(10)(vi) § 63.7540(a)(112) § 63.7540(a)(13)	boiler or process heater must be conducted every 5 years as specified in §	§ 63.7515(d) § 63.7540(a) § 63.7540(a)(10)(i) § 63.7540(a)(10)(ii) § 63.7540(a)(10)(iii) § 63.7540(a)(10)(iv) § 63.7540(a)(10)(v) [G]§ 63.7540(a)(10)(vi) [G]§ 63.7540(c)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(a)(2) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(e) § 63.7530(f) § 63.7540(b) § 63.7545(a) § 63.7545(c) [G]§ 63.7545(c) [G]§ 63.7545(e) § 63.7550(a) [G]§ 63.7550(b) [G]§ 63.7550(c) [G]§ 63.7550(h)
CLEANUP	PRO	R5461	VOC	30 TAC Chapter 115, Subchapter E, Division 6	[G]§ 115.461(d) [G]§ 115.463(c)	The following are exempt from the VOC limits in §115.463(a) of this title (relating to Control Requirements): §115.461(d)(1)-(17)	None	§ 115.468(b)(2) § 115.468(b)(5)	None
DTANK	EU	R5217	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land- based operations). All land- based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
DTANK	EU	R5111	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FWC	EP	R5122	voc	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(A)	Vent gas streams affected by §115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None
FWC	PRO	63WWWW 2	112(B) HAPS	40 CFR Part 63, Subpart WWWW	§ 63.5790(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart WWWW
FWP1	EP	R5122	voc	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(A)	Vent gas streams affected by §115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None
FWP1	PRO	63WWWW	112(B) HAPS	40 CFR Part 63, Subpart WWWW	§ 63.5790(a) The permit holder shall comply with the applicable limitation, standard and/or equipment	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable monitoring and testing requirements of 40	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart WWWW

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					specification requirements of 40 CFR Part 63, Subpart WWWW		CFR Part 63, Subpart WWWW	www	
FWPSTYTK	EU	R5127	voc	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land- based operations). All land- based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
FWPSTYTK	EU	R5111	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GEN	EU	63ZZZZ1	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(f)
GEN	EU	63ZZZZ3	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of	None	None	§ 63.6645(f)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).			
GRPCASTM IX	EU	R5111	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPCASTR TK	EU	R5217	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
GRPCASTR TK	EU	R5111	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPCFLEX TK	EU	R5217	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPCFLEX TK	EU	R5111	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPFWPMI X	EU	R5111	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPFWPRT K	EU	R5217	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land- based operations). All land- based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
GRPFWPRT K	EU	R5111	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPNCMIX	EU	R5111	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPNCRTK	EU	R5217	voc	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
GRPNCRTK	EU	R5111	voc	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
MAIN	EP	R5122	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(A)	Vent gas streams affected by §115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None
MAIN	PRO	63WWWW 1	112(B) HAPS	40 CFR Part 63, Subpart WWWW	§ 63.5790(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart WWWW

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
NCPIPE	EP	R5122	voc	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(A)	Vent gas streams affected by §115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None
NCPIPE	PRO	63WWWW 3	112(B) HAPS	40 CFR Part 63, Subpart WWWW	§ 63.5790(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart WWWW	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart WWWW

	Permit Shield	
Permit Shield	2	3

### **Permit Shield**

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
BOILER	N/A	40 CFR Part 60, Subpart Dc	Boiler is less than 10 MMBtu/hr
DTANK	N/A	40 CFR Part 60, Subpart Kb	Tank has a capacity of less than 19,800 gallons.
GEN	N/A	40 CFR Part 60, Subpart IIII	Constructed or modified/reconstructed before 7/11/2005.
GRPCASTMIX	FR-MIXER1, FR-MIXER2, FR- MIXER3, FR-MIXER4	40 CFR Part 60, Subpart Kb	Tanks have capacities of less than 19,800 gallons.
GRPCASTRTK	RTK1, RTK2, RTK3, RTK4, RTK5, RTK6, RTK7, RTK8	40 CFR Part 60, Subpart Kb	Tanks have capacities of less than 19,800 gallons.
GRPCFLEXTK	RFLXTK1, RFLXTK2, RFLXTK3, RFLXTK4	40 CFR Part 60, Subpart Kb	Tanks have capacities of less than 19,800 gallons.
GRPNCMIX	NCMIX1, NCMIX2, NCMIX3, NCMIX4	40 CFR Part 60, Subpart Kb	Tanks have capacities of less than 19,800 gallons.
GRPNCRTK	NCRTK1, NCRTK2, NCRTK3	40 CFR Part 60, Subpart Kb	Tanks have capacities of less than 19,800 gallons.
GTANK	N/A	30 TAC Chapter 115, Storage of VOCs	Tank has a capacity of less than 1000 gallons.
GTANK	N/A	40 CFR Part 60, Subpart Kb	Tank has a capacity of less than 19,800 gallons.
PARTWASH	N/A	30 TAC Chapter 115, Degreasing Processes	Solvent vapor pressure is less than 0.6 psia at 100 degrees Fahrenheit.

### **New Source Review Authorization References**

New Source Review Authorization References	25
New Source Review Authorization References by Emission Unit	26

### **New Source Review Authorization References**

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Pe By Rule, PSD Permits, or NA Permits) for the	rmits, and Other Authorizations (Other Than Permits Application Area.
Authorization No.: 55013	Issuance Date: 02/10/2020
Authorization No.: 162442	Issuance Date: 10/02/2020
Authorization No.: 165428	Issuance Date: 07/15/2021
Permits By Rule (30 TAC Chapter 106) for the	Application Area
Number: 106.183	Version No./Date: 09/04/2000
Number: 106.227	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.265	Version No./Date: 09/04/2000
Number: 106.266	Version No./Date: 09/04/2000
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.412	Version No./Date: 09/04/2000
Number: 106.452	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
BOILER	BOILER	106.183/09/04/2000
CLEANUP	CLEANING SOLVENT	55013
DC-10	SPENCER VACUUM SYSTEM	106.262/11/01/2003 [165077]
DC-4	MAIN SHOP PIPE GRINDER DUST COLLECTOR	106.266/09/04/2000 [86099]
DC-5	SECONDAR SHOP PIPE GRINDER DUST COLLECTOR	106.266/09/04/2000 [86099]
DC-6	COUPLING GRINDER DUST COLLECTOR	106.266/09/04/2000 [91794]
DC-9	NC PIPE GRINDER DUST COLLECTOR	106.262/11/01/2003 [163329]
DTANK	DIESEL TANK	106.473/09/04/2000 [166507]
FR-MIXER1	CASTING MIX TANKS	106.473/09/04/2000 [165715]
FR-MIXER2	CASTING MIX TANKS	106.473/09/04/2000 [165715]
FR-MIXER3	CASTING MIX TANKS	106.473/09/04/2000 [165715]
FR-MIXER4	CASTING MIX TANKS	106.473/09/04/2000 [165715]
FWC	FILAMENT WINDING COUPLING PROCESS	55013
FWP-MIXER1	FILAMENT WINDING MIX TANK #1	55013
FWP-MIXER2	FILAMENT WINDING MIX TANK #2	55013
FWP-MIXER3	FILAMENT WINDING MIX TANK #3	55013
FWP-MIXER4	FILAMENT WINDING MIX TANK #4	55013
FWP1	FILAMENT WINDING MACHINE #1	55013
FWPRTK1	FILAMENT WINDING BULK RESIN TANK #1	55013
FWPRTK2	FILAMENT WINDING BULK RESIN TANK #2	55013
FWPRTK3	FILAMENT WINDING BULK RESIN TANK #3	55013

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
FWPSTYTK	FILAMENT WINDING BULK STYRENE TANK	55013
GEN	DIESEL ENGINE	106.511/09/04/2000 [76043, 152180]
GTANK	GASOLINE TANK	106.473/09/04/2000 [166507]
JOINTLUBE	PIPE JOINT LUBRICANT	106.261/11/01/2003 [167814]
MAIN	CENTRIFUGAL CASTING PROCESS	55013
NCMIX1	NC PIPE MIX TANK #1	55013
NCMIX2	NC PIPE MIX TANK #2	55013
NCMIX3	NC PIPE MIX TANK #3	55013
NCMIX4	NC PIPE MIX TANK #4	55013
NCPIPE	NC PIPE MANUFACTURING PROCESS	55013
NCRTK1	NC PIPE RESIN TANK #1	55013
NCRTK2	NC PIPE RESIN TANK #2	55013
NCRTK3	NC PIPE RESIN TANK #3	55013
PARTWASH	COLD SOLVENT CLEANER	106.454/11/01/2001 [74232]
RFLXTK1	CASTING RESIN FLEX TANK #1	106.262/11/01/2003 [165905]
RFLXTK2	CASTING RESIN FLEX TANK #2	106.262/11/01/2003 [165905]
RFLXTK3	CASTING RESIN FLEX TANK #3	106.262/11/01/2003 [165905]
RFLXTK4	CASTING RESIN FLEX TANK #4	106.262/11/01/2003 [165905]
RTK1	CASTING RESIN STORAGE TANK #1	106.473/09/04/2000 [165905]
RTK2	CASTING RESIN STORAGE TANK #2	106.473/09/04/2000 [165905]
RTK3	CASTING RESIN STORAGE TANK #3	106.473/09/04/2000 [165905]

#### **New Source Review Authorization References by Emissions Unit**

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
RTK4	CASTING RESIN STORAGE TANK #4	106.473/09/04/2000 [165905]
RTK5	CASTING RESIN STORAGE TANK #5	106.473/09/04/2000 [165905]
RTK6	CASTING RESIN STORAGE TANK #6	106.473/09/04/2000 [165905]
RTK7	CASTING RESIN STORAGE TANK #7	106.473/09/04/2000 [165905]
RTK8	CASTING RESIN STORAGE TANK #8	106.473/09/04/2000 [165905]
SEC-WG#1	SECONDARY WATER GRINDER #1	106.265/09/04/2000 [167815]
SEC-WG#2	SECONDARY WATER GRINDER #2	106.265/09/04/2000 [167815]
WG-RECT	FWP OFFLINE RECTIFICATION	106.262/11/01/2003 [169211]
WP-GRV	FWP GROOVER	106.262/11/01/2003 [169211]

<sup>\*\*</sup>This column may include Permit by Rule (PBR) numbers and version dates, PBR Registration numbers in brackets, Standard Permit Registration numbers, Minor NSR permit numbers, and Major NSR permit numbers.

	Appendix A	
Acronym List		3

## **Acronym List**

The following abbreviations or acronyms may be used in this permit:

$\Lambda \cap \Box \Lambda \Lambda$	actual cubic feet per minute
	alternate means of control
	Acid Rain Program
	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
	control device
	continuous emissions monitoring system
	continuous opacity monitoring system
CVS	closed vent system
D/FW	
	emission point
	U.S. Environmental Protection Agency
	emission unit
EU	ernission unit
	Federal Clean Air Act Amendments
	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	
	hydrogen sulfide
	identification number
	pound(s) per hour
MACT	Maximum Achievahla Control Technology (40 CEP Part 63)
	Million British thermal units per hour
MMBtu/hr	
MMBtu/hrNA	
MMBtu/hr NA N/A	
MMBtu/hr NA N/A NADB	
MMBtu/hrNAN/ANADBNESHAP	
MMBtu/hrNAN/ANADBNESHAPNOx	
MMBtu/hr	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base  National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60)  New Source Review  Office of Regulatory Information Systems
MMBtu/hr	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base  National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60)  New Source Review  Office of Regulatory Information Systems  lead  Permit By Rule
MMBtu/hr	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base  National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60) New Source Review  Office of Regulatory Information Systems  lead  Permit By Rule  predictive emissions monitoring system
MMBtu/hr	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base  National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60)  New Source Review  Office of Regulatory Information Systems lead  Permit By Rule  predictive emissions monitoring system particulate matter
MMBtu/hr	
MMBtu/hr	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base  National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60)  New Source Review  Office of Regulatory Information Systems lead  Permit By Rule  predictive emissions monitoring system particulate matter
MMBtu/hr	
MMBtu/hr	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60) New Source Review  Office of Regulatory Information Systems  lead  Permit By Rule  predictive emissions monitoring system particulate matter  parts per million by volume  process unit  prevention of significant deterioration
MMBtu/hr	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base  National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60) New Source Review  Office of Regulatory Information Systems lead  Permit By Rule  Permit By Rule  predictive emissions monitoring system particulate matter  parts per million by volume  process unit  prevention of significant deterioration  pounds per square inch absolute
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PM PPM PPM PPSD PSD PSia SIP	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base  National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60) New Source Review  Office of Regulatory Information Systems lead  Permit By Rule  Permit By Rule  predictive emissions monitoring system particulate matter  parts per million by volume process unit  process unit prevention of significant deterioration pounds per square inch absolute state implementation plan
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PM PRO PSD PSIA SIP SO2	Million British thermal units per hour nonattainment not applicable  ———————————————————————————————————
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PEMS PM ppmv PRO PSD psia SIP SO2 TCEQ	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60) New Source Review  Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PM ppmv PRO PSD psia SIP SO2 TCEQ TSP	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)  nitrogen oxides  New Source Performance Standard (40 CFR Part 60)  New Source Review  Office of Regulatory Information Systems  lead  Permit By Rule  predictive emissions monitoring system  particulate matter  parts per million by volume  process unit  prevention of significant deterioration  pounds per square inch absolute  state implementation plan  sulfur dioxide  Texas Commission on Environmental Quality total suspended particulate
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PM PRO PSD PSIA SIP SO2 TCEQ TSP TVP	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)  nitrogen oxides  New Source Performance Standard (40 CFR Part 60)  New Source Review  Office of Regulatory Information Systems  lead  Permit By Rule  predictive emissions monitoring system  particulate matter  parts per million by volume  process unit  prevention of significant deterioration  pounds per square inch absolute  state implementation plan  sulfur dioxide  Texas Commission on Environmental Quality  total suspended particulate  true vapor pressure
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PM ppmv PRO PSD psia SIP SO2 TCEQ TSP TVP U.S.C.	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides  New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration punds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate true vapor pressure United States Code
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PM ppmv PRO PSD psia SIP SO2 TCEQ TSP TVP U.S.C.	Million British thermal units per hour nonattainment not applicable  National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)  nitrogen oxides  New Source Performance Standard (40 CFR Part 60)  New Source Review  Office of Regulatory Information Systems  lead  Permit By Rule  predictive emissions monitoring system  particulate matter  parts per million by volume  process unit  prevention of significant deterioration  pounds per square inch absolute  state implementation plan  sulfur dioxide  Texas Commission on Environmental Quality  total suspended particulate  true vapor pressure